

PREMIUM TABLETOP INKJET MARKER

JetBox-700



DESCRIPTION

JetBox-700 is a PREMIUM desktop inkjet printer (marker-encoder) with integrated large format (7") color touch-screen control panel. Thanks to the large display, it is possible to create print files on the machine without having to use a PC. Up to 1000 files can be stored in the machine's memory. JetBox-700 can accommodate either 12.7mm or 25.4mm print cartridges (pens). With a simple tool you can change the printer configuration from 12.7 or 25.4, independently. Thanks to the possibility of installing 2 heads, printing areas of as much as

DESCRIPTION

50.8mm can be reached. Cartridges with different types of ink can be used: water-based, solvent-based, coloured (water-based only). Printing costs are very low, let's calculate that with a standard solvent-based cartridge it is possible to print about 250,000 labels with date/time/Expiration in Arial10 characters. Of course, ink consumption is proportional to the type of printing you do. The presence of an encoder guarantees the precision of the position, the repetition and correctness of the prints even with 1D or 2D barcodes (QRcode).



TECHNICAL FEATURES

DESCRIPTION	JetBox-700
PRINTING AREA	Up to 25.14mm
PRINTING POINT HEIGHT	from 0 to 80mm
FIXING HEAD	Exclusive quick fastening system
PRINTING LENGHT	Up to 500mm
PRINTING DEFINITION	Up to 300 dpi
PRINTING SPEED	Up to 70 mt/min. Automatically adjusted by encoder.
CARTRIDGES	HP type TIJ2.5
CARTRIDGES TYPE	Water-based and Solvent-based (black, white).
CONTENTS	Texts, numbers, time, dates, logo, QRcode, barcode, etc.
FONTS	All windows fonts loadable via USB
ROW NUMBER	No limits
VERTICAL PRINTING	Yes, freely rotatable
PRINTING DEFINITION	+/- 1mm
COMMEND PANEL	7" color touch-screen
PRINTING DIRECTION	From right to left
LANGUAGES	Italiano, Inglese, Tedesco, Spagnolo, Russo, Cinese, Turco, Arabo, Coreano
MEMORY	Fino a 1000 file
MICROPROCESSOR	Yes, with integrated clock
TRANSPARENT OBJECT	Yes
TRANSPARENT OBJECT	Yes
POWER SUPPLY	220/110 Vac—12 Vdc 4A 48W
WEIGHT	16 Kg
DIMENSION	40x38x35(H) cm
OPERATING TEMPERATURES	From 0 a 45°C. to 40-60% umidity
COSTRUCTION	Aisi304 stainless steel, steel, aluminum

Packin